

Intermittent Bagmaker **S250/300**




Intermittent Bagmaker S250/300 In Detail


What's better than a highly reliable bagger with a repeatable delivery? One that's also incredibly fast. Meet the S250/300, an impressive vertical form, fill and seal machine that provides the stainless steel sanitary design and affordability you've come to expect from our S Series. Want efficiency? With speeds up to 150 bags per minute, faster, repeatable and accurate production runs will be the norm. Want consistency? The S250/300 prevents bottlenecking. Want flexibility? The S250/300 accommodates several bag styles, including quad-seal. Want peace of mind? Make the S250/300 your next investment.



- Robust, stainless steel frame
- Siemens or Allen Bradley control system
- Servo-drive jaw actuation
- Open frame design
- Off-the-shelf components
- Minimal maintenance requirements
- Short film path
- Small machine footprint
- No tool changeover
- Self-centering pull belts
- Automatic film tracking
- VFD powered film unwind
- Quick film splice table
- Photo eye and encoder
- Automatic machine stop
- Jaw obstruction detection
- Runs most film structures
- Storage for 100 product recipes

Machine drawings





options



- Upgrade 300 mm bad width
- Continuous motion mode
- Ultrasonic sealing jaws
- Quad seal bag assembly
- Servo pull belts actuation
- Flat bottom bag assembly
- Impulse sealing for poly film structures
- Washdown IP66 construction
- Vacuum pull belts
- Fold-down/tape-down unit
- Hole punch (Euroslot and Round)
- Load shelf
- Product settler
- Gas flush
- Static elimination
- Tear notch
- Product stagers
- End-seal cooling air
- **Bag deflators**
- Degassing valve applicator
- **Remote diagnostics**
- Zipper applicator
- Bag-in-bag configuration
- Integration with variety of fillers, printers, metal detectors, label applicators, and checkweighers
- In-feed and take-away conveyors

Max. speed


150 bpm

Weight 950 kg (2,095 lbs)

Air pressure 6 bar (15–18 CFM at 90 PSI)

Bag length

Power supply 7.9 kVA







Europe, Asia, Africa, Australia **IKING MASEK**

Viking Mašek, a.s. | Průmyslová 1747 | 258 01 Vlašim | Czech Republic Phone + 420 317 850 500 | Email info@masek.cz | Website www.masek.cz, www.vikingmasek.cz North and South America

Viking Masek Packaging Technologies, Inc. | 40 Woodland Court | Oostburg, WI 53070 | USA Phone + 1 920 564 5051 | Email sales@vikingmasek.com | Website www.vikingmasek.com

Bag width 50–250/300 mm

(1.96"-9.84"/11.81")

60–400 mm (2.38"-15.75")