

Viking Masek Flow Wrapper Synchropack-60



The Syncrhopack-60 (bottom film reel holder) servo-driven machine is the ideal solution for irregular, fragile, frozen, sticky or difficult to move products.

Featuring a robust machine build, cantilever design, modular construction, high flexibility & performance, ease of operation & changeover, low maintenance cost.



200 bpm



max. 270 × 550 mm (10,72" × 21.65")

min. 10 × 50 mm (0.39" × 1.96")



7 configurations



Flow Wrapper 60 In Detail

Featuring a robust machine build, cantilever design, modular construction, high flexibility & performance, ease of operation & changeover, low maintenance cost.

This common platform has been used to develop multiple configurations that combined with a wide range of available accessories allow the Pack 600 to be adapted to many different products as well as to the most demanding requirements in a wide range of production environments.

Our extensive experience also enables us to offer a wide number of accessories and feeding systems for a variety of different products.



- Pusher conveyor
- Bottom reel holder
- Universal forming box
- Fin longitudinal sealing unit
- End cutting and welding unit
- Outfeed conveyor
- Transmission cabinet
- 10.4" Touch Screen (HMI)
- Easy changeover
- Modular construction
- Minimal maintenance requirements
- Automatic film splice
- Robust stainless steel build





- Poly configuration for polyethylene films
- Cold configuration for cold sealing films
- Box Motion configuration for hermetic sealing
- Robotic handling for right hand execution Integration with feeders
- Integration with ancillary equipment



200 bpm

Weight

1000 - 1500 kg (2205 - 3307 lb)

Bag width

10 - 270 mm (0.39" - 10.62") Air pressure

(15–18 CFM at 90 PSI)

Bag length Power supply

50 - 550 mm 380-440 VAC / 3 Ph / 50-60 HZ (1.96" - 21.65")









