

Viking Masek Flow Wrapper FW-90



The FW-90 (top film reel holder) is a servodriven solution designed to package standard products. It accommodates manual, semiautomatic, or automatic feeding and allows for numerous format changes.

Featuring a robust machine build, cantilever design, modular construction, high flexibility & performance, Ease of operation & changeover, low maintenance cost and servo-driven controls, are the main features of this model of wrapping machine.



bag size 200 bpm

max. 270 × 550 mm (10,72" × 21.65")

min. 10 x 50 mm (0.39" × 1.96")



7 configurations

Flow Wrapper 90 In Detail

This versatile platform supports a multitude of configurations. Coupled with an array of available accessories, the FW-90 seamlessly integrates with numerous products, meeting the most stringent demands across various production environments. Leveraging our extensive experience, we also provide a broad selection of accessories and feeding systems to accommodate a diverse array of product types.

Max. speed

200 bpm

Weight

6 bar

1000 - 1500 kg (2205 - 3307 lb)

Air pressure

Bag length 50 - 550 mm

(15-18 CFM at 90 PSI)

Power supply

380-440 VAC / 3 Ph / 50-60 H7



- Pusher conveyor
- Top reel holder -
- Universal forming box
- Fin longitudinal sealing unit
- End cutting and welding unit
- Outfeed conveyor
- Transmission cabinet
- 10.4" Touch Screen (HMI)
- Easy changeover
- Modular construction
- Minimal maintenance requirements
- Automatic film splice
- Robust stainless steel build



- Poly configuration for polyethylene films
- Cold configuration for cold sealing films Box
- Motion configuration for hermetic sealing
- Robotic handling for right hand execution
- Integration with feeders
- Integration with ancillary equipment



00000

Machine drawing





US Headquarters

Viking Masek Packaging Technologies, Inc. | 40 Woodland Court | Oostburg, WI 53070 | USA Phone +1920 564 5051 | Email sales@vikingmasek.com | Website www.vikingmasek.com

Bag width

10 - 270 mm (0.39" - 10.62")

(1,96" - 21,65")



