

Viking Masek Flow Wrapper Synchropack-90



The Synchropack-90 (top film reel holder) is a servo-driven solution designed to package standard products. It accommodates manual, semi-automatic, or automatic feeding and allows for numerous format changes.

Featuring a robust machine build, cantilever design, modular construction, high flexibility & performance, Ease of operation & changeover, low maintenance cost and servo-driven controls, are the main features of this model of wrapping machine.





max. 270 × 550 mm (10,72" × 21.65")

min. 10 x 50 mm (0.39" × 1.96")



7 configurations



Flow Wrapper 90 In Detail

This versatile platform supports a multitude of configurations. Coupled with an array of available accessories, the Synchropack-90 seamlessly integrates with numerous products, meeting the most stringent demands across various production environments. Leveraging our extensive experience, we also provide a broad selection of accessories and feeding systems to accommodate a diverse array of product types.

Max. speed

200 bpm

Weight

1000 - 1500 kg (2205 - 3307 lb)

Bag width

10 - 270 mm (0.39" - 10.62")

Air pressure

(15-18 CFM at 90 PSI)

Bag length

50 - 550 mm (1,96" - 21,65")

Power supply


380-440 VAC / 3 Ph / 50-60




- Pusher conveyor
- Top reel holder
- Universal forming box
- Fin longitudinal sealing unit
- End cutting and welding unit
- Outfeed conveyor
- Transmission cabinet
- 10.4" Touch Screen (HMI)
- Easy changeover
- Modular construction
- Minimal maintenance requirements
- Automatic film splice
- Robust stainless steel build



- Poly configuration for polyethylene films
- Cold configuration for cold sealing films Box
- Motion configuration for hermetic sealing
- Robotic handling for right hand execution
- Integration with feeders
- Integration with ancillary equipment





Machine drawing

