

Viking Masek Flow Wrapper FW-600



The FW-600, with its bottom film reel holder and servo-driven functionality, serves as the perfect solution for handling products that are irregular, delicate, frozen, adhesive, or challenging to maneuver.


Featuring a robust machine build, cantilever design, modular construction, high flexibility & performance, ease of operation & changeover, low maintenance cost.



500 bpm



max. 270 × 550 mm (10,72" × 21.65")









Flow Wrapper 600 In Detail

Featuring a robust machine build, cantilever design, modular construction, high flexibility & performance, ease of operation & changeover, low maintenance cost.

This common platform has been used to develop multiple configurations that combined with a wide range of available accessories allow the 6-series to accommodate a variety of products as any and all production environments.

Our extensive experience also enables us to offer a wide number of accessories and feeding systems for a variety of different products.

features

- Pusher conveyor
- Bottom reel holder
- Universal forming box
- Fin longitudinal sealing unit
- End cutting and welding unit
- Longitudinal welding module
- Outfeed conveyor
- Transmission cabinet
- 10.4" Touch Screen (HMI)
- Easy changeover
- Modular construction
- Minimal maintenance requirements
- Automatic film splice
- Robust stainless steel build





- Poly configuration for polyethylene films
- Cold configuration for cold sealing films
- Box Motion configuration for hermetic sealing
- Robotic handling for right hand execution Integration with feeders
- Integration with ancillary equipment



500 bpm

Weight

1000 - 1500 kg (2205 - 3307 lb)

Bag width

10 - 270 mm (0.39" - 10.62") Air pressure

(15-18 CFM at 90 PSI)

Bag length

50 - 550 mm (1,96" - 21,65") Power supply

380-440 VAC / 3 Ph / 50-60 HZ

