

Multilane Stickpack Machine **ST400**



Our ST400 machines are economical stickpack solutions, maintaining all the advantages of their larger brothers. ST400 machines offer you flexibility, versatility, performance, ruggedness, high quality and reliability, and first class service.



65 cpm



max. 40 × 200 mm (1.57" × 7.88") min. 17 × 40 mm (0.67" × 1.57")

















Bag Types



Bag Options




Multilane Stickpack Machine ST400 In Detail


Looking for an economical solution for your stickpack needs? Our versatile multilane ST400 stickpack can accommodate from 1 to 10 lanes to form different shapes of stickpack pouches. Designed to pack powders; dense, fine, loose and particulate materials as well as liquids into stickpack bags and to accommodate different bag shapes including pour spouts, tear notches and easy-open system. Semi- or fully automated cartoning solutions are also available for individual or bulk cartoning.



- Film unwind with film tension control
- Film slitters and forming tubes set per bag size
- Discharge chutes
- Siemens control system
- Automatic film tracking
- Integrated inner light
- Easy change-over™

Machine drawings





options

$O \otimes O$

- Straight cut
- Zigzag cut
- Round cut
- Multi-lane volumetric filler, servo auger filler or servo liquid fillers
- Easy change-over parts and stainless storage cart
- Easy open features like tear notch or microperforation
- Various seal patterns and shapes
- Offset back seal
- Automatic stickpack length adjustment
- Individual discharge chutes
- **Empty stick detection**
- Empty stick rejection
- Dust suction nozzles
- Static elimination
- Film edge trimming and suction
- Embossing in the longitudinal seal
- Stainless steel construction
- Pharma construction (IO/OO)
- Robotic pick-and-place unit and automatic cartoning solutions
- Hot stamp, Inkjet, or thermal transfer
- In-feed and out-feed conveyors



65 cpm

Weight

Bag width

17-40 mm

6 bar

(0.67"-1.57")

(15 CFM at 90 PSI)

600 kg (1,325 lbs)

Air pressure

Bag length

40-200 mm (1.57"-7.88") Power supply

6 kVA







